

# **BOTTOM-MOUNTED REACH-IN REFRIGERATOR**



Toll Free Number: 1 (800) 931-8628



Email: Info@dukersusa.com



Website: www.dukersusa.com

MODEL: D55R-GS2

## Features and Benefits

- \* Higher Resistance to Dust , high quality condenser
- \* R290 Natrual Refrigerant, promotes faster cool down and efficient energy consumption
- \* 3-year parts and labor, 5-year compressor warranty
- \* Stainless steel inside and outside, sealed interior floors and rounder cabinet corners for easy cleaning
- \* Self-closing doors with stay open feature.
- \* Adjustable, heavy duty shelves

## Technical Specifications

Voltage/Frequency	115V/60Hz	
Refrigerant	R290	
Type of Defrost	Automatic	
Exterior Finish	Stainless steel	
Interior Finish	Stainless steel	
Net Weight	463 lbs	
Total Capacity	40.74 cu ft	
Total Current	8.6A	
Climatic Category	4/5	
Nema Config.	5-15P	











MODEL NO	TEMPERATURE RANGE (°F )	EXTERNAL DIMENSION WXDXH(INCHES)	PACKING, CARTON WXDXH (INCHES)	DOOR	40GP CONTAINER CERTIFICATION
D55R-GS2	33°F ~ 41°F	551/8" X 325/8" X 803/8"	56¾" X 34¼" X 84%"	2	21

# **BOTTOM-MOUNTED** REACH-IN REFRIGERATOR

## **MODEL: D55R-GS2**

Model: D55R-GS2

115V AC Rated Voltage:

60Hz Rated Frequency:

730W Total Input Power:

8.6A **Total Current:** 

Total Capacity: 40.74 cu ft

Refrigerant: R290/4.58oz

Climatic Category: 4/5

**Protection Type** 1

Design pressure High Side: 300PSIG

Low Side:150PSIG

Insulation Blowing Gas C-pentane

Net Weight: 463 lbs

**NEMA Config** 5-15P

#### STANDARD FEATURES

#### BOTTOM MOUNT COMPRESSOR

The bottom mount compressor structure is placed in the coolest possible area, provides quick and easy service R-Series

#### HIGH QUALITY STEEL

Interior and exterior high quality steel minimizes dents, scratches and rust

### HIGH DENSITY POLYURETHANE **INSULATION CFC**

free and high density cell foam is Eco-friendly and more energy efficient

STURDY, CLEAN STAINLESS SHELVING

High quality coated stainless shelves may prevent peel and rust.

SELF-CLOSING DOOR SYSTEM


Door Automatically close at 60°


REFRIGERATORS HOLDS 33 °F - 41 °F

FOR BEST IN REFRIGERATORS

115/60/1

### **PLAN VIEW**









FRONT VIEW



