



ELECTRIC

SPEC SERIES 36" RANGES WITH GRIDDLE TOP

IMPERIAL



IHR-GT24-2-E

Shown with optional casters

MODEL NUMBERS

IHR-GT24-2-E
IHR-GT24-2-E-C
IHR-GT24-2-E-XB
IHR-GT24-2-E-M
IHR-GT36-E
IHR-GT36-E-C
IHR-GT36-E-XB
IHR-GT36-E-M

GRIDDLE TOP

- Thick highly polished 3/4" (19 mm) steel plate with thermostat controls.
- 21" (533 mm) plate depth.
- Even heating elements across the griddle section provide consistent temperature across the plate.
- 4" (102 mm) wide grease trough and removable grease can for easy cleaning.
- Large griddle grease can is removable for easy cleaning.

ELECTRIC ROUND PLATE ELEMENTS

- Sealed 2.6 KW round plate elements with easy-to-clean surface
- Provides a solid flat surface for fast, even heating
- Plates are 9" (229) diameter for maximum pan contact
- Solid top prevents spills from entering unit making clean-up easy
- Infinite heat controls for maximum cooking flexibility

CONVECTION OVEN

- Unique heat baffles assure even cooking throughout the entire oven.
- Creates an air flow that circulates the air throughout all interior surfaces of the oven cavity
- Fast temperature recovery
- 1/4 hp fan motor for high production cooking.
- 4 oven racks included with 8 rack guide positions for maximum versatility.
- Stainless steel sides, top and legs are standard.

STANDARD OVEN

- High performance 5 KW element provides even heating throughout the oven interior.
- Unique baffle above the element distributes heat flow to provide even cooking temperatures
- throughout the 5.3 KW oven. Splatter screen protects the element from spills.
- Chef depth standard oven interior accommodates standard 18" x 26" (457 x 660 mm) sheet pans front-to-back and side-by-side.
- Oven is 26½" w x 26" d x 14" h (673 x 660 x 356 mm).
- Heavy duty thermostat with temperature range from 150F to 500°F (65°C to 260°C).
- Porcelainized sides, rear, deck and door lining.
- Stamped inner door liner provides extra strength while optimizing heat retention.
- One chrome oven rack is included.

IMPERIAL


1128 Sherborn Street | Corona, CA 92879 | 800.343.7790 | imperialrange.com | imperialsales@imperialrange.com

©2024 Imperial Commercial Cooking Equipment Imperial reserves the right to change specifications at any time without prior notice and without any obligation for past or future equipment purchases. Visit www.imperialrange.com for specification updates



ELECTRIC

SPEC SERIES 36" RANGES WITH GRIDDLE TOP



DIMENSIONS: 36" (914) W X 38" (965) D
ELECTRICAL OUTPUT: 17.3 KW

ELECTRICAL REQUIREMENTS

MODEL	TOTAL KW	VOLTS	PHASE	AMPS	SHIP WEIGHT
IHR-GT24-2-E	17.3	208	1	84	(277)610
	17.3	208	3	49	(277)610
	17.3	240	1	73	(277)610
	17.3	240	3	48	(277)610
	17.3	*480	3	21	(277)610
IHR-GT24-2-E-C	17.3	208	1	91	(304) 670
	17.3	208	3	56	(304) 670
	17.3	240	1	80	(304) 670
	17.3	240	3	55	(304) 670
	17.3	*480	3	28	(304) 670
IHR-GT24-2-E-XB	12	208	1	58	(200) 440
	12	208	3	34	(200) 440
	12	240	1	50	(200) 440
	12	240	3	29	(200) 440
	12	*480	3	15	(200) 440
IHR-GT24-2-E-M	12	208	1	58	(152) 335
	12	208	3	34	(152) 335
	12	240	1	50	(152) 335
	12	240	3	29	(152) 335
	12	*480	3	15	(152) 335

MODEL	TOTAL KW	VOLTS	PHASE	AMPS	SHIP WEIGHT
IHR-GT36-E	17.3	208	1	84	(277) 610
	17.3	208	3	49	(277) 610
	17.3	240	1	73	(277) 610
	17.3	240	3	48	(277) 610
	17.3	*480	3	21	(277) 610
IHR-GT36-E-C	17.3	208	1	91	(304) 670
	17.3	208	3	56	(304) 670
	17.3	240	1	80	(304) 670
	17.3	240	3	55	(304) 670
	17.3	*480	3	28	(304) 670
IHR-GT36-E-XB	12	208	1	58	(200) 440
	12	208	3	34	(200) 440
	12	240	1	50	(200) 440
	12	240	3	29	(200) 440
	12	*480	3	15	(200) 440
IHR-GT36-E-M	12	208	1	58	(152) 335
	12	208	3	34	(152) 335
	12	240	1	50	(152) 335
	12	240	3	29	(152) 335
	12	*480	3	15	(152) 335

NOTE: Measurements in () are metric equivalents.

ELECTRIC CONVECTION OVEN OPTIONS

- Cook and Hold Feature
- Heavy Duty Casters, set of 4
- Stainless Steel Bottom Shelf and Adjustable Rack Supports
- Extra Standard Depth Oven Racks
- 480 volt motor
- Stainless Steel solid doors available at no additional charge. Must specify at ordering.

*Additional charge

CLEARANCE REQUIREMENTS

For use only on non-combustible floors. Legs or casters are required for non-combustible floors; or 2 1/4" (57 mm) overhang is required when curbmounted. Provide 0" clearance from non-combustible surfaces and 6" (152 mm) from combustible surfaces.

Two speed motor - 1/2 HP, 1725/1140 RPM.



MADE IN USA

IMPERIAL

1128 Sherborn Street | Corona, CA 92879 | 800.343.7790 | imperialrange.com | imperialsales@imperialrange.com

© 2024 Imperial Commercial Cooking Equipment Imperial reserves the right to change specifications at any time without prior notice and without any obligation for past or future equipment purchases. Visit www.imperialrange.com for specification updates