

## Blixer® 5 V.V.



5.5 L

**A SALES FEATURES**

Blixer 5 V.V. is designed to prepare texture-modified meals with either raw and cooked ingredients in a minimum of time.

**B TECHNICAL FEATURES**

Blixer 5 V.V. Single-phase. Power: 3 HP. Variable speed: 300-3500 rpm. 5.5 L stainless-steel bowl with handle, plus bowl-base, fine-serrated, twin-blade assembly. Totally leakproof lid with scraper arm. 3 – 18 portions (7 oz.).


Select your options at the back page, **F** part.

**C TECHNICAL DATA**

Output power	3 HP
Electrical data	120V/60/1 - 15 Amps
Variable speed	300-3500 rpm
Dimensions (WxDxH)	11" x 13 13/16" x 19 11/16" Cube: 3.68
Rate of recyclability	95%
Net weight	49 lbs
Nema #	5-20P
Reference	BLIXER 5 V.V. - 120V/60/1

**D**

Number of 7 oz portions per service



Amount processed per operation

0.75 to 7 lbs

**E PRODUCT FEATURES / BENEFITS****MOTOR UNIT**

- Industrial direct-drive (no belt) induction motor designed for intensive use
- Power 3 HP
- Stainless-steel motor shaft
- All-metal motor base
- Magnetic safety system, thermal failsafe.
- Variable speed 300-3500 rpm

**BLIXER® FUNCTION**

- 5.5 L stainless-steel bowl with handle for better grip.
- Bowl-base blade assembly with two high-strength, stainless-steel, fine-serrated blades for homogeneous processing – even for small amounts.
- Central lid opening for adding liquid or solid ingredients during processing.
- High heat and shock-resistant see-through lid to monitor processing from start to finish.
- Leakproof lid and bowl unit with bowl scraper arm and lid wiper.
- All parts are dishwasher-safe and can easily be removed for cleaning.

**STANDARD ATTACHMENTS**

- 5.5 L bowl with lid.
- Bowl scraper arm and lid wiper.
- Blade assembly with two fine-serrated, stainless-steel blades and a detachable cap.

**STANDARDS**

ETL electrical and sanitation Listed/ cETL (Canada)



## Blixer® 5 V.V.

F

- Fine serrated edge stainless steel "S" blade assembly  
Ref. 27155
- Coarse serrated edge stainless steel "S" blade assembly  
Ref. 27180
- 5.5 L Stainless steel bowl assembly - Ref. 27165

G

## ELECTRICAL DATA

120V/60/1 - delivered with cord and plug.

