BOTTOM-MOUNTED REACH-IN REFRIGERATOR

MODEL: D55R

Model: **D55R**

115V AC Rated Voltage:

60Hz Rated Frequency:

Total Input Power: 730W

Total Current: 8.6A

Total Capacity: 40.74 cu ft

Refrigerant: R290/4.58oz

Climatic Category: 4/5

Protection Type

Design pressure High Side: 300PSIG

Low Side:150PSIG

Insulation Blowing Gas C-pentane

Net Weight: 463 lbs

NEMA Config 5-15P

STANDARD FEATURES

BOTTOM MOUNT COMPRESSOR

The bottom mount compressor structure is placed in the coolest possible area, provides quick and easy service R-Series

HIGH QUALITY STEEL

Interior and exterior high quality steel minimizes dents, scratches and rust

HIGH DENSITY POLYURETHANE INSULATION CFC

free and high density cell foam is Eco-friendly and more energy efficient

STURDY, CLEAN STAINLESS SHELVING

High quality coated stainless shelves may prevent peel and rust.

SELF-CLOSING DOOR SYSTEM


Door Automatically close at 60°

REFRIGERATORS HOLDS 33 °F - 41 °F

FOR BEST IN REFRIGERATORS

NEMA 5-15P 115/60/1

PLAN VIEW







FRONT VIEW



BOTTOM-MOUNTED REACH-IN REFRIGERATOR



Toll Free Number: 1 (800) 931-8628



Email: Info@dukersusa.com



Website: www.dukersusa.com

MODEL: D55R

Features and Benefits

- * High Resistance to Dust , high quality condenser
- * R290 Natrual Refrigerant, promotes faster cool down and efficient energy consumption
- * 3-year parts and labor, 5-year compressor warranty
- * Stainless steel inside and outside, sealed interior floors and rounder cabinet corners for easy cleaning
- * Self-closing doors with stay open feature.
- * Adjustable, heavy duty shelves

Technical Specifications

Voltage/Frequency	115V/60Hz
Refrigerant	R290
Type of Defrost	Automatic
Exterior Finish	Stainless steel
Interior Finish	Stainless steel
Net Weight	463 lbs
Total Capacity	40.74 cu ft
Total Current	8.6A
Climatic Category	4/5
Nema Config.	5-15P











