

## **UPRIGHT SHOWCASE MERCHANDISER**



Toll Free Number: 1 (800) 931-8628



Email: Info@dukersusa.com



Website: www.dukersusa.com

MODEL: DSM-48R

## Features and Benefits

- \* Digital temperature control features, a digital display to make monitoring interior temperature a breeze
- \* 2-year parts and labor, 5-year compressor warranty
- \* Auto defrost function, which ensures optimal performance day-in and day-out
- \* Interior LED Lighting on the right side to always show your products at their best
- \* Anti-fogging tempered glass door helps ensure a crystal clear view of the interior

### **Technical Specifications**

Voltage/Frequency	115V/60Hz		
Refrigerant	R290		
Type of Defrost	Automatic		
Exterior Finish	Stainless steel		
Interior Finish	Stainless steel		
Net Weight	451lbs		
Total Capacity	48.73 cu ft		
Total Current	9.8A		
Climatic Category	4/5		
Nema Config.	5-15P		











MODEL NO	TEMPERATURE RANGE (°F)	EXTERNAL DIMENSION WXDXH(INCHES)	PACKING, CARTON WXDXH (INCHES)	DOOR	40GP CONTAINER CERTIFICATION
DSM-48R	32°F ~ 50°F	541/8" X 311/8" X 791/2"	55½" X 33¼" X 81%"	2	22

# UPRIGHT SHOWCASE MERCHANDISER

## **MODEL:DSM-48R**

Model: DSM-48R

Rated Voltage: 115V AC

Rated Frequency: 60Hz

Total Input Power: 690W

Total Current: 9.8A

Total Capacity: 48.73 cu ft

Refrigerant: R290/5.11oz

Climatic Category: 4/5

Protection Type I

Design pressure High Side :300PSIG

Low Side: 150PSIG

Insulation Blowing Gas C-pentane

Net Weight: 451 lbs

NEMA Config 5-15P

#### STANDARD FEATURES

#### **BOTTOM MOUNT COMPRESSOR**

bottom mount compressor structure is placed in the coolest possible area, provides quick and easy service

#### HIGH QUALITY STEEL

interior and exterior uses high-quality steel to minimizes dents, scratches and rust

## HIGH DENSITY POLYURETHANE INSULATION CFC

free and high density cell foam is Eco-friendly and more energy efficient

STURDY, CLEAN STAINLESS SHELVING high quality coated stainless shelves prevents peel and rust.


SELF-CLOSING DOOR SYSTEM door Automatically close at 60°


MERCHANDIZERS OPERATE AT

32 °F - 50 °F

## NEMA 5-15P 115/60/1

#### **PLAN VIEW**





SIDE VIEW





FRONT VIEW

California Office 2488 Peck Road, City of Industry, CA 90601 (562) 568-4060 www.dukersusa.com New Jersey Office 475 S Clinton Ave South Plainfield, NJ 07080 (800) 608-9289 Info@dukersusa.com

Georgia Office 6513 Warren Dr NW Norcross, GA 30093 (678) 580-3960 service@dukersusa.com Texas Office 1444 N Cockrell Hill Rd #104 Dallas, TX 75211 (469) 421-1040 Warrenrty@dukersusa.com