




NEO[®] 240 Undercounter Ice Machines

50Hz UDP-0240A UYP-0240A



U-240 Undercounter Ice Machine

- Ranging from 68 kgs (150 lbs) to 87 kgs (191 lbs) daily ice production
 - Only 66.04 cm (26") wide, 72.4 cm (28.5") deep, and 97.8 cm (38.5") high on 15.24 cm (6") legs
 - Cabinet volume 0.086 m³ (3.037 ft³)
 - 40 kgs (90 lbs) ice storage capacity*
- * Application capacity based on: 90% volume x 33lbs/ft³ average density of ice.

NEO undercounter ice machines are designed to provide ice right where you need it – within reach. Improvements in Performance, Intelligence and Convenience make your ice machine easy to own and less expensive to operate.

Performance – NEO produces more ice than ever before while using less water and energy. The storage bin provides industry leading capacity.

Intelligence – NEO provides feedback with full bin and service indicators. Delay function allows you to pause your machine for slow periods or days when you're closed.

Convenience – NEO offers a forward-sliding storage bin for easy access to refrigeration components without having to move the entire ice machine. Smooth, sealed foodzone with removable water trough, distribution tube, and damper door for faster cleaning. AlphaSan added to key internal components.

Available **LuminIce[®]** Virus and Bacteria Inhibitor controls viruses, bacteria, mold and yeast within the food zone to keep the machine clean longer.



Specifications

BTU Per Hour:
U-240: 2,932 (average)
3,496 (peak)

Compressor:
Nominal rating: .33 HP

Refrigerant:
R290

Operating Limits:
• Ambient Temperature Range:
4.4° to 43.3° C (40° to 110° F)

• Water Temperature Range:
4.4° to 32.2° C (45° to 90° F)

• Water Pressure Ice Maker
Water In:
Min. 20 psi (137.9 kPa)
Max. 80 psi (551.1 kPa)

Ice Shape



Dice
2.22 x 2.22 x 2.22 cm
(7/8" x 7/8" x 7/8")



Half Dice
.95 x 2.86 x 2.22 cm
(3/8" x 1 1/8" x 7/8")

Ice Machine Electric

230/50/1 ice machines are factory pre-wired with a 180 CM (6') power cord only, no plug is supplied.

Total Amps:
U-240A - 4.0 AMPS

Maximum fuse size:
Air-cooled: 15 amps

HACR-type circuit breakers can be used in place of fuses.




Manitowoc Ice reserves the right to make changes to the design or specifications without prior notice.

GERMANY
Welbilt Deutschland
Auf der Weih 1135745
Herborn, Germany
Tel: +49 2772 58050

SPAIN
Textil, 6 - Pol. Ind. La Ferreria - 08110
Montcada i Reixac, Barcelona Spain
Tel: +34 902 20 10 69

UNITED KINGDOM
Welbilt UK
Ashbourne House
The Guildway, Old Portsmouth Rd
Guildford GU3 1LR United Kingdom
Tel: +44 1483 464 900

www.manitowocice.com



Installation Note Recommended clearance for top, sides, and back is 5" (12.7 cm) however, there is no minimum clearance required.


- Ⓐ Electrical Entrance
- Ⓑ 3/8" (0.95 cm) F.P.T. Ice Making Water Inlet
- Ⓒ 1/2" (1.27 cm) F.P.T. Minimum Water Condenser Outlet (water-cooled units)
- Ⓓ 3/8" (0.95 cm) F.P.T. Water Condenser Inlet (water-cooled units)
- Ⓔ 1/2" (1.27 cm) F.P.T. Ice Bin Drain

Specifications

Model	Ice Shape	Ice Production 24 Hours				Power Usage kWh / 45.5 kgs of ice @ 32°/21°C	Potable Water Usage Liters/45.5 kgs. ice @ 32°/21°C
		70°Air/50°F Water 21°Air/10°C Water		90°Air/70°F Water 32°Air/21°C Water			
UYPO240A	half-dice	191 lbs	87 kg	150 lbs	68 kg	7.2	89
UDPO240A	dice	191 lbs	87 kg	150 lbs	68 kg	7.2	81

Standard 6" / 15.24 cm adjustable flange foot - gray painted legs included.
Standard plastic NEO ice scoop included.

Accessories / Features

<p>LuminIce® II Virus and Bacteria Inhibitor controls viruses and bacteria inside the ice machine.</p> 	<p>Arctic Pure® Plus Water Filters reduce sediments and chlorine contaminants down to .5 microns. Use with a Pre-filter is recommended.</p> 	<p>Removable Bin allows for easier service.</p> 	<p>Air Flow Air in right, air out left, no side vents. Great for installation under countertops and next to other equipment.</p> 
---	--	---	---

GERMANY
Welbilt Deutschland
Auf der Weih 1135745
Herborn, Germany
Tel: +49 2772 58050

SPAIN
Textil, 6 - Pol. Ind. La Ferreria - 08110
Montcada i Reixac, Barcelona Spain
Tel: +34 902 20 10 69

UNITED KINGDOM
Welbilt UK
Ashbourne House
The Guildway, Old Portsmouth Rd
Guildford GU3 1LR United Kingdom
Tel: +44 1483 464 900

www.manitowocice.com
7240B 06/22