

UNDER COUNTER FREEZER



Toll Free Number: 1 (800) 931-8628



Email: Info@dukersusa.com



Website: www.dukersusa.com

MODEL: DUC48F

Features and Benefits

- * Higher Restistance to Dust , high quality condenser
- * R290 Natrual Refrigerant, promotes faster cool down and efficient energy consumption
- * 3-year parts and labor, 5-year compressor warranty
- * Stainless steel inside and outside, sealed interior floors and rounder cabinet corners for easy cleaning
- * Self-closing doors with stay open feature.
- * Adjustable, heavy duty shelves



| Voltage/Frequency | 115V 60Hz | |
|-------------------|-----------------|--|
| Refrigerant | R290 | |
| Type of Defrost | Automatic | |
| Exterior Finish | Stainless steel | |
| Interior Finish | Stainless steel | |
| Net Weight | 211lbs | |
| Total Capacity | 12.21 cu ft | |
| Total Current | 8.0A | |
| Climatic Category | 4/5 | |
| Nema Config. | 5-15P | |











| MODEL NO | TEMPERATURE RANGE (°F) | EXTERNAL DIMENSION WXDXH(INCHES) | PACKING,CARTON WXDXH(INCHES) | DOOR | 40GP CONTAINER CERTIFICATION |
|----------|-----------------------------|----------------------------------|---------------------------------|------|---------------------------------|
| DUC48F | 0 °F - 8 °F | 481/8"X 311/2" X 36 | 49%" X 33%" X 39%" | 2 | 46 |

UNDER COUNTER FREEZER

MODEL: DUC48F

Model: DUC48F

Rated Voltage: 115V AC

Rated Frequency: 60Hz

Total Input Power: 660W

Total Current: 8.0A

Total Capacity: 12.21 cu ft

Refrigerant: R290/3.70oz

Climatic Category: 4/5

Protection Type I

Design pressure High Side :300PSIG

Low Side:150PSIG

Insulation Blowing Gas C-pentane

Net Weight: 211 lbs

NEMA Cofig. 5-15P

STANDARD FEATURES

BACK MOUNT COMPRESSOR

The back mount compressor structure is placed in the coolest possible area, provides quick and easy service

HIGH QUALITY STEEL

Interior and exterior uses high quality steel minimizes dents, scratches and rust

HIGH DENSITY POLYURETHANE INSULATION CFC

free and high density cell foam is Eco-friendly and more energy efficient

STURDY, CLEAN STAINLESS SHELVING high quality coated stainless shelves

prevent peel and rust.


SELF-CLOSING DOOR SYSTEM door Automatically close at 60°


FREEZERS OPERATE AT

0 °F - 8 °F



PLAN VIEW





SIDE VIEW





FRONT VIEW

California Office 2488 Peck Road, City of Industry, CA 90601 (562) 568-4060 www.dukersusa.com New Jersey Office 475 S Clinton Ave South Plainfield, NJ 07080 (800) 608-9289 Info@dukersusa.com

Georgia Office 6513 Warren Dr NW Norcross, GA 30093 (678) 580-3960 service@dukersusa.com Texas Office 1444 N Cockrell Hill Rd #104 Dallas, TX 75211 (469) 421-1040 Warrenrty@dukersusa.com