

UPRIGHT SHOWCASE MERCHANDISER



Toll Free Number: 1 (800) 931-8628



Email: Info@dukersusa.com



Website: www.dukersusa.com

MODEL: DSM-32SR

Features and Benefits

- * Digital temperature control features, a digital display to make monitoring interior temperature a breeze
- * 2-year parts and labor, 5-year compressor warranty
- * Auto defrost function, which ensures optimal performance day-in and day-out
- * Interior LED Lighting on the right side to always show your products at their best
- * Anti-fogging tempered glass door helps ensure a crystal clear view of the interior

Technical Specifications

Voltage/Frequency	115V/60Hz
Refrigerant	R290
Type of Defrost	Automatic
Exterior Finish	Black
Interior Finish	White
Net Weight	339 lbs
Total Capacity	33.49 cu ft
Total Current	3.8A
Climatic Category	4/5
Nema Config.	5-15P











MODEL NO	TEMPERATURE RANGE (°F)	EXTERNAL DIMENSION WXDXH(INCHES)	PACKING, CARTON WXDXH (INCHES)	DOOR	40GP CONTAINER CERTIFICATION
DSM-32SR	32°F ~ 50°F	39% X 32" X 79½"	48¾" X 33¾" X 81¾"	2	28

UPRIGHT SHOWCASE MERCHANDISER

MODEL: DSM-32SR

Model: DSM-32SR

Rated Voltage: 115V AC

Rated Frequency: 60Hz

Total Input Power: 430W

Total Current: 3.8A

Total Capacity: 33.29 cu ft

Refrigerant: R290/5.11oz

Climatic Category: 4/5

Protection Type I

Design pressure High Side :300PSIG

Low Side:150PSIG

Insulation Blowing Gas C-pentane

Net Weight: 339lbs

NEMA Config 5-15P

STANDARD FEATURES

BOTTOM MOUNT COMPRESSOR

The bottom mount compressor structure is placed in the coolest possible area, provides quick and easy service R-Series

HIGH QUALITY STEEL

Interior and exterior high quality steel minimizes dents, scratches and rust

HIGH DENSITY POLYURETHANE INSULATION CFC

free and high density cell foam is Eco-friendly and more energy efficient

STURDY, CLEAN STAINLESS SHELVING

High quality coated stainless shelves may prevent peel and rust.


SELF-CLOSING DOOR SYSTEM


Door Automatically close at 60°

MERCHANDISER HOLDS 32 °F - 50 °F FOR BEST IN MERCHANDISER

NEMA 5-15P 115/60/1

PLAN VIEW





SIDE VIEW





FRONT VIEW