TOP-MOUNTED REACH-IN REFRIGERATOR

MODEL: D83AR

Model: D83AR Rated Voltage: 115V AC Rated Frequency: 60Hz Total Input Power: 760W **Total Current:** 8.6 **Total Capacity:** 64.80 cu ft R290/5.22 oz Refrigerant: Climatic Category: 4/5 **Protection Type**

Design pressure High Side :300PSIG

Low Side:150PSIG

Insulation Blowing Gas C-pentane
Net Weight: 595 lbs

NEMA Config 5-20P

STANDARD FEATURES

TOP MOUNT COMPRESSOR

The top mount compressor structure is placed in the coolest possible area, provides quick and easy service

HIGH QUALITY STEEL

Interior and exterior high quality steel minimizes dents, scratches and rust

HIGH DENSITY POLYURETHANE INSULATION CFC

free and high density cell foam is Eco-friendly and more energy efficient


STURDY, CLEAN STAINLESS SHELVING High quality coated stainless shelves may prevent peel and rust.


SELF-CLOSING DOOR SYSTEM
Door Automatically close at 60°

REFRIGERATORS OPERATE AT 33 °F - 41 °F



PLAN VIEW





SIDE VIEW

AQ AutoQuotes



FRONT VIEW

California Office 2488 Peck Road, City of Industry, CA 90601 [562] 568-4060 www.dukersusa.com New Jersey Office 475 S Clinton Ave South Plainfield, NJ 07080 (800) 608-9289 Info@dukersusa.com Georgia Office 6513 Warren Dr NW Norcross, GA 30093 (678) 580-3960 service@dukersusa.com

Texas Office 1444 N Cockrell Hill Rd #104 Dallas, TX 75211 (469) 421-1040 Warrentty@dukersusa.com



TOP-MOUNTED REACH-IN REFRIGERATOR



Toll Free Number: 1 (800) 931-8628 Email: Info@dukersusa.com





Website: www.dukersusa.com

MODEL: D83AR

Features and Benefits

- * High Resistance to Dust, high quality condenser
- * R290 Natrual Refrigerant, promotes faster cool down and efficient energy consumption
- * 3-year parts and labor, 5-year compressor warranty
- * Stainless steel inside and outside, sealed interior floors and rounder cabinet corners for easy cleaning
- * Self-closing doors with stay open feature.
- * Adjustable, heavy duty shelves



Voltage/Frequency	115V/60Hz		
Refrigerant	R290		
Type of Defrost	Automatic		
Exterior Finish	Stainless steel		
Interior Finish	Stainless steel		
Net Weight	595lbs		
Total Capacity	64.80 cu ff		
Total Current	8.6		
Climatic Category	4/5		
Nema Config.	5-20P		











MODEL NO	TEMPERATURE RANGE (°F)	EXTERNAL DIMENSION WXDXH(INCHES)	PACKING, CARTON WXDXH (INCHES)	DOOR	40GP CONTAINER CERTIFICATION
D83AR	33 °F - 41 °F	82%" X 32%" X 80%"	841/4" X 341/4" X 843/6"	3	13